according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Buntlack Innen Außen Anthrazitgr seiden.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Alpina Farben GmbH

Roßdörfer Straße 50

64372 OBER RAMSTADT

Telephone : +498001238887 Telefax : +4961547170632

Website : www.alpina-farben.de E-mail address Responsi- : msds@dr-rmi.com

ble/issuing person

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Additional Labeling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-

isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an aller-

gic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Polyacrylate-based lacquer, aqueous

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-methylpentane-2,4-diol	107-41-5 203-489-0 603-053-00-3 01-2119539582-35	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d	>=1-<3
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 603-096-00-8 01-2119475104-44	Eye Irrit. 2; H319	>= 1 - < 10
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 ——— M-Factor (Acute aquatic toxicity): 1	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

		M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	>= 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
manganese ferrite black spinel	68186-94-7 269-056-3 01-2119457599-19		>= 1 - < 10

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Use water spray to cool unopened containers.

Standard procedure for chemical fires. The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only with adequate ventilation.

For personal protection see section 8.

No special technical protective measures required.

Please follow the technical information.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
manganese ferrite	68186-94-7	AGW (Inhalable	0,2 mg/m3	DE TRGS
black spinel		fraction)	(Manganese)	900
	Peak-limit cat	egory: 8;(II)		
	Further inform	nation: For Permanga	anates an excursion factor of	1(II) applies.,
	When there is	compliance with the	e OEL and biological tolerand	e values, there
	is no risk of ha	arming the unborn ch	nild	
		AGW (Alveolate	0,02 mg/m3	DE TRGS
		fraction)	(Manganese)	900
	Peak-limit cat	egory: 8;(II)		
			anates an excursion factor of	1(II) applies.,
	When there is	compliance with the	OEL and biological tolerand	e values, there
	is no risk of ha	arming the unborn ch	nild	
		TWA (inhalable	0,2 mg/m3	2017/164/EU
		fraction)	(Manganese)	
	Further inform	nation: Indicative		
		TWA (Respirable	0,05 mg/m3	2017/164/EU
		fraction)	(Manganese)	
	Further information: Indicative			
		MAK (measured	0,02 mg/m3	DE DFG MAK
		as the alveolate		
		fraction)		
	Further information: Damage to the embryo or foetus is unlikely when the			
	MAK value or the BAT value is observed, Permanganates: Peak limitation			
	category I(1)			
		MAK (inhalable	0,2 mg/m3	DE DFG MAK
		fraction)		
	Further information: Damage to the embryo or foetus is unlikely when the			
	MAK value or the BAT value is observed, Permanganates: Peak limitation			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

	category I(1)			
2-methylpentane-	107-41-5	MAK	10 ppm	DE DFG MAK
2,4-diol			49 mg/m3	
	Further inform	ation: Either there a	re no data for an assessmen	t of damage to
	the embryo or foetus, including developmental neurotoxicity, or the currently			
	available data are not sufficient for classification in one of the groups A - C			
2-(2-	112-34-5	TWA	10 ppm	2006/15/EC
butoxyeth-			67,5 mg/m3	
oxy)ethanol				
	Further inform	ation: Indicative		
		STEL	15 ppm	2006/15/EC
			101,2 mg/m3	
	Further inform	nation: Indicative		
		AGW (Vapour	10 ppm	DE TRGS
		and aerosols)	67 mg/m3	900
	Peak-limit cat	egory: 1.5;(I)		
			compliance with the OEL ar	nd biological
			of harming the unborn child	Ü
		MAK	10 ppm	DE DFG MAK
			67 mg/m3	
	Further inform	nation: Damage to th	e embryo or foetus is unlikely	when the
	MAK value or	the BAT value is ob	served	
titanium dioxide; [in	13463-67-7	MAK (measured	0,3 mg/m3	DE DFG MAK
powder form con-		as the alveolate		
taining 1 % or		fraction)		
more of particles				
with aerodynamic				
diameter ≤ 10 µm]				
	Peak-limit category: 8; II			
	Further information: Substances that cause cancer in humans or animals or			
			enic for humans and for which	
	can be derived., Damage to the embryo or foetus is unlikely when the MAK			
	value or the BAT value is observed			T
		AGW (Inhalable	10 mg/m3	DE TRGS
		fraction)	(Titanium dioxide)	900
	Peak-limit cat			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)	(Titanium dioxide)	900
	Peak-limit category: 2;(II)			
		Further information: When there is compliance with the OEL and biological		
	tolerance valu		of harming the unborn child	DE TD00
		BM (Alveolar	0,5 mg/m3	DE TRGS
]	dust fraction)		527

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
manganese ferrite black spinel	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

	Workers	Inhalation	Long-term local effects	10,00 mg/m3
Silicic acid, aluminum sodium salt	Workers	Inhalation	Long-term local ef- fects	4,00 mg/m3
2-methylpentane-2,4-diol	Consumers	Inhalation	Long-term local ef- fects	25,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	3,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,00 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	49,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,00 mg/kg bw/day
	Workers	Inhalation	Acute local effects	98,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	14,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	49,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	2,00 mg/kg bw/day
2-(2- butoxyethoxy)ethanol	Consumers	Inhalation	Acute local effects	60,70 mg/m3
	Consumers	Ingestion	Long-term systemic effects	5,00 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef- fects	40,50 mg/m3
	Consumers	Skin contact	Long-term systemic effects	50,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	40,50 mg/m3
	Workers	Inhalation	Acute local effects	101,20 mg/m3
	Workers	Inhalation	Long-term systemic effects	67,50 mg/m3
	Workers	Inhalation	Long-term local ef- fects	67,50 mg/m3
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

	, , , , , , , , , , , , , , , , , , , ,	
Substance name	Environmental Compartment	Value
2-methylpentane-2,4-diol	Soil	0,11 mg/kg dry weight (d.w.)
	Intermittent use/release	4,29 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

	Secondary Poisoning	100 mg/kg food
	Fresh water sediment	1,79 mg/kg dry
		weight (d.w.)
	Sea water	0,0429 mg/l
	Sewage treatment plant	20 mg/l
	Sea sediment	0,179 mg/kg dry
		weight (d.w.)
	Fresh water	0,429 mg/l
2-(2-butoxyethoxy)ethanol	Fresh water	1,1 mg/l
	Fresh water sediment	4,4 mg/kg dry
		weight (d.w.)
	Intermittent use/release	11 mg/l
	Sea water	0,11 mg/l
	Sea sediment	0,44 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	200 mg/l
	Soil	0,32 mg/kg dry
		weight (d.w.)
	Secondary Poisoning	56 mg/kg food
titanium dioxide; [in powder form	Sewage treatment plant	100 mg/l
containing 1 % or more of parti-		
cles with aerodynamic diameter ≤		
10 μm]		
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry
		weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sea sediment	100 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,193 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Long sleeved clothing

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Safety shoes

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

DGUV Regulation 112-190 - Use of breathing equipment

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : gray

Odor : characteristic

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8 - 9 (20 °C)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

Concentration: 100 %

Method: DIN EN ISO 19396-1:2020-05

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Flow time : not determined

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,1 g/cm3 (20 °C)

Method: DIN EN ISO 2811-1

Bulk density : Not applicable

Relative vapor density : not determined

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

2-(2-butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2.410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2.764 mg/kg

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified based on available information.

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version **Revision Date:** SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

: 1

M-Factor (Chronic aquatic

toxicity)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic tox- : 100

M-Factor (Chronic aquatic

toxicity)

100

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n-

log Pow: 0,56

octanol/water

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: nlog Pow: 0,63 - 0,76

octanol/water pH: 7

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: n- : log Pow: <= 0,75

octanol/water Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of liquid material residues at the collection point for

old paints/varnishes, dispose of dried material residues as construction and demolition waste or as municipal waste or

household waste.

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regu-

lations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75

If you intend to use this product as tattoo ink, please contact your vendor.

dor.

REACH - Candidate List of Substances of Very High

Concern for Authorization (Article 59).

: None

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

Not applicable

Water hazard class (Germa-

ny)

WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

: M-LW01 Water-based varnishes

: BSW30 Coating materials, water-based, containing solvents

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,12 %

Volatile organic compounds : Directive 2004/42/EC

< 4 % < 50 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version **Revision Date:** SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin.

Causes severe skin burns and eye damage. H314

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. Causes serious eye damage. H318 Causes serious eye irritation. H319

Fatal if inhaled. H330

Suspected of causing cancer if inhaled. H351 H361d Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. H411

Corrosive to the respiratory tract. **EUH071**

Full text of other abbreviations

Acute Tox. Acute toxicity

Short-term (acute) aquatic hazard Aquatic Acute Long-term (chronic) aquatic hazard Aquatic Chronic

Carc. Carcinogenicity Eve Dam. Serious eve damage

Eye Irrit. Eye irritation

Repr. Reproductive toxicity Skin Corr. Skin corrosion Skin Irrit. Skin irritation Skin Sens. Skin sensitization

Europe. Indicative occupational exposure limit values 2006/15/EC 2017/164/EU Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values

Germany, MAK BAT Annex IIa

DE DFG MAK

DE TRGS 527 Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 Germany. TRGS 900 - Occupational exposure limit values.

2006/15/EC / TWA Limit Value - eight hours 2006/15/EC / STEL Short term exposure limit Limit Value - eight hours 2017/164/EU / TWA

MAK value DE DFG MAK / MAK

DE TRGS 527 / BM Assessment scale DE TRGS 900 / AGW Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage riage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Covid International Congenization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Pollution from Pollution From Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed

Further information

Other information

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the Ger-

man Social Accident Insurance)
Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Buntlack Innen Außen Anthrazitgr seiden.

Version Revision Date: SDS Number: Date of last issue: 12.06.2024 2.2 30.09.2024 6004944 Date of first issue: 28.10.2019

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN