according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Voll- und Abtönfarbe Color Lucky Yellow

Unique Formula Identifier : PG6N-HQSW-D01C-2M0D

(UFI)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Alpina Farben GmbH

Roßdörfer Straße 50

64372 OBER RAMSTADT

Telephone : +498001238887 Telefax : +4961547170632

Website : www.alpina-farben.de E-mail address Responsi- : msds@dr-rmi.com

ble/issuing person

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : P101

If medical advice is needed, have product con-

tainer or label at hand.

P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing mist or vapors.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Additional Labeling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Emulsion paint, aqueous

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

VersionRevision Date:SDS Number:Date of last issue: 20.02.20253.511.07.20256007789Date of first issue: 10.12.2019

	Index-No. Registration number		
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17		>= 1 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
		specific concentration limit Skin Sens. 1A; H317 >= 0,036 %	
		Acute toxicity esti-	
		Acute oral toxicity: 450 mg/kg Acute inhalation tox- icity (dust/mist): 0,21 mg/l	
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

VersionRevision Date:SDS Number:Date of last issue: 20.02.20253.511.07.20256007789Date of first issue: 10.12.2019

		specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
Pyridine-2-thiol 1-oxide, sodium salt	3811-73-2 223-296-5 613-344-00-7 01-2119493385-28	Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT RE 1; H372 (Nervous system) Aquatic Acute 1; H400 Aquatic Chronic 2; H411 EUH070 M-Factor (Acute aquatic toxicity): 100 Acute toxicity estimate Acute oral toxicity: 500 mg/kg Acute inhalation tox-	>= 0,0002 - < 0,0025
		icity (dust/mist): 0,5 mg/l Acute dermal toxicity: 790 mg/kg	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0002 - < 0,0015
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
3.5	11.07.2025	6007789	Date of first issue: 10.12.2019

		specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
Substances with a workplace expos	sure limit :		
barium sulfate	7727-43-7		>= 1 - < 10
	231-784-4		
	01-2119491274-35		
kaolin	1332-58-7		>= 1 - < 10
	310-194-1		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Standard procedure for chemical fires.

The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

No special technical protective measures required.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
barium sulfate	7727-43-7 MAK (measured as the alveolate fraction)		0,3 mg/m3	DE DFG MAK	
	Peak-limit category: 8; II				
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value				

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

VersionRevision Date:SDS Number:Date of last issue: 20.02.20253.511.07.20256007789Date of first issue: 10.12.2019

		d., Damage to the e	mbryo or foetus is unlikely d	when the MAK		
		MAK (inhalable fraction)	4 mg/m3	DE DFG MAK		
	Peak-limit category: 8; II					
	Further information: Substances that cause cancer in humans or animals that are considered to be carcinogenic for humans and for which a MAK v					
	can be derive	can be derived., Damage to the embryo or foetus is unlikely when the MAK				
	value or the B	AT value is observe				
		AGW (Inhalable	10 mg/m3	DE TRGS		
		fraction)		900		
	Peak-limit cat					
			compliance with the OEL			
	tolerance valu		of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900		
	Peak-limit cat					
			s compliance with the OEL			
	tolerance valu		of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527		
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC		
	Further inform	nation: Carcinogens	or mutagens			
titanium dioxide	13463-67-7	MAK (measured	0,3 mg/m3	DE DFG MAK		
		as the alveolate				
		fraction)				
Peak-limit category: 8; II						
			hat cause cancer in human			
			enic for humans and for w			
			mbryo or foetus is unlikely	when the MAK		
	value or the B	AT value is observe		DE TROO		
		AGW (Inhalable	10 mg/m3	DE TRGS		
	Dook limit oot	fraction)	(Titanium dioxide)	900		
	Peak-limit cat		s compliance with the OEL	and higherical		
		ies, there is no risk o	of harming the unborn child			
		AGW (Alveolate	1,25 mg/m3	DE TRGS		
	<u> </u>	fraction)	(Titanium dioxide)	900		
	Peak-limit cat		n			
			compliance with the OEL			
	tolerance valu		of harming the unborn child			
		BM (Alveolar	0,5 mg/m3	DE TRGS		
Duriding O thick 4	2011 72 2	dust fraction)	0.2 m a/m2	527		
Pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	MAK (inhalable fraction)	0,2 mg/m3	DE DFG MAK		
ONIUG, SUUIUIII SAIL	Peak-limit cat	,				
		· ·	corntian through the akin.	Damage to the		
			sorption through the skin, I the MAK value or the BAT			
	served	,				

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

	fraction)		900
	Peak-limit category: 2;(II)		
	Further information: Skin absorption, When there is compliance with the OEL		
	and biological tolerance values, there is no risk of harming the unborn child		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
titanium dioxide	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
2-[(2-methoxy-4- nitrophenyl)azo]-N-(2- methoxyphenyl)-3- oxobutyramide	Consumers	Ingestion	Long-term systemic effects	25,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	25,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	49,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	42,00 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
barium sulfate	Fresh water	115 μg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Soil	207,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
titanium dioxide	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

DGUV Regulation 112-190 - Use of breathing equipment

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : yellow

Odor : No data available

Melting point/freezing point : ca. 0 °C

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper :

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

: not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8

Concentration: 100 %

Viscosity

Viscosity, dynamic : No data available

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

Not applicable

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,3000 g/cm3

Relative vapor density : Not applicable

9.2 Other information

Explosives : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Acute toxicity estimate: 450 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,21 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Pyridine-2-thiol 1-oxide, sodium salt:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,5 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 790 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version **Revision Date:** SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified based on available information.

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1

icity)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

M-Factor (Chronic aquatic

toxicity)

: 1

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- :

icity)

M-Factor (Chronic aquatic :

toxicity)

. '

Pyridine-2-thiol 1-oxide, sodium salt:

M-Factor (Acute aquatic tox- : 100

icity)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

100

barium sulfate:

Toxicity to fish : Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox-

icity)

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: No toxicity at the limit of solubility.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n- : log Pow: 0,63 - 0,76

octanol/water pH: 7

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

2-methylisothiazol-3(2H)-one:

Partition coefficient: n- : log Pow: -0,486 (25 °C)

octanol/water pH: 7

Pyridine-2-thiol 1-oxide, sodium salt:

Partition coefficient: n- : Pow: 0,002 (20 °C)

octanol/water

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: n- : log Pow: <= 0,75

octanol/water Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Materials and all related packaging must be disposed of in a

safe way in accordance with the full requirements of the local,

regional, national and international authorities.

Washing water must not be discharged into the sewage sys-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

tem or the environment.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version **Revision Date:** SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks Not classified as dangerous in the meaning of transport regu-

lations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

2-[(2-methoxy-4-nitrophenyl)azo]-N-(2-methoxyphenyl)-3-oxobutyramide

(Number on list 75)

REACH - Candidate List of Substances of Very High

Concern for Authorization (Article 59) (SVHC).

None

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

Not applicable

ny)

Water hazard class (Germa: WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

: Coating materials, water-based

Labeling according to Regu-: Treated article, contains a biocidal product. In-can preserva-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

lation (EU) 528/2012 tive: CIT/MIT (3:1), BIT, MIT.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 0,02 %

Volatile organic compounds : Directive 2004/42/EC

< 0.1 % < 1 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H330 : Fatal if inhaled. H331 : Toxic if inhaled.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

EUH070 : Toxic by eye contact.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

Eye Irrit.: Eye irritationSkin Corr.: Skin corrosionSkin Irrit.: Skin irritationSkin Sens.: Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens, mutagens

or reprotoxic substances at work - Annex III

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2004/37/EC / TWA : Long term exposure limit

DE DFG MAK / MAK : MAK value

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EMS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals Ships; Inc. - International Conditions (IMO - International Convention) organization; IECSC - Inventional Code for the Construction of Ships; Inc. - International Code for the Construction of Ships; Inc. - International Convention for the Prevention of Pollution from Ships; Inc. - International

Further information

Other information

: No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation.

2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the Ger-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Voll- und Abtönfarbe Color Lucky Yellow

Version Revision Date: SDS Number: Date of last issue: 20.02.2025 3.5 11.07.2025 6007789 Date of first issue: 10.12.2019

man Social Accident Insurance)
Toxnet - Toxicology Data Network

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN