according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Silikat Fassadenfarbe

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Alpina Farben GmbH

Roßdörfer Straße 50

64372 OBER RAMSTADT

Telephone : +498001238887 Telefax : +4961547170632

Website : www.alpina-farben.de E-mail address Responsi- : msds@dr-rmi.com

ble/issuing person

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

### **Additional Labeling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Due to its potassium silicate content, the reaction of silicate based coatings is highly alkaline. Hence protect skin and eyes from paint.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Emulsion paint, aqueous

Components

Chemical name	CAS-No. EC-No. Index-No.	Classification	Concentration (% w/w)	
Silicic acid, potassium salt	Registration number 1312-76-1 215-199-1 01-2119456888-17	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335  specific concentration limit Skin Irrit. 2; H315 >= 40 % Eye Irrit. 2; H319 >= 40 % STOT SE 3; H335 >= 75 %	>= 1 - < 10	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10	
cristobalite (respirable dust)[MX]	14464-46-1 238-455-4	STOT RE 1; H372	>= 1 - < 10	
Substances with a workplace exposure limit :				
cristobalite	14464-46-1 238-455-4		>= 1 - < 10	
Talc (Mg3H2(SiO3)4)	14807-96-6		>= 1 - < 10	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

> 238-877-9 01-2120140278-58

This substance is integrated into the matrix of our products and will therefore be ignored for classification and labeling of the product.

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Take off all contaminated clothing immediately.

Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

Unsuitable extinguishing

media

None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

#### 5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Use water spray to cool unopened containers.

Standard procedure for chemical fires. The product itself does not burn.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

No special technical protective measures required.

Please follow the technical information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

### **Occupational Exposure Limits**

				1	
Components	CAS-No.	Value type (Form	Control parameters	Basis	
-		of exposure)			
cristobalite	14464-46-1	TWA (Respirable	0,1 mg/m3	2004/37/EC	
		dust)	,		
T-1-		Further information: Carcinogens or mutagens			
Talc	14807-96-6	AGW (Inhalable	10 mg/m3	DE TRGS	
(Mg3H2(SiO3)4)		fraction)		900	
	Peak-limit cate	egory: 2;(II)			
	Further information: When there is compliance with the OEL and biological				
	tolerance valu	es, there is no risk of	of harming the unborn child	-	
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)	_	900	
	Peak-limit category: 2;(II)				
	Further information: When there is compliance with the OEL and biological			nd biological	
	tolerance values, there is no risk of harming the unborn child			_	
titanium dioxide; [in	13463-67-7	MAK (measured	0,3 mg/m3	DE DFG MAK	
powder form con-		as the alveolate			
taining 1 % or		fraction)			
more of particles		naonon)			
with aerodynamic					
diameter ≤ 10 µm]					
	Peak-limit category: 8; II				
	Further information: Substances that cause cancer in humans or animals or				

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

	that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW (Inhalable	10 mg/m3	DE TRGS
		fraction)	(Titanium dioxide)	900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)	(Titanium dioxide)	900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar	0,5 mg/m3	DE TRGS
		dust fraction)		527
cristobalite (respir-	14464-46-1	TWA (Respirable	0,1 mg/m3	2004/37/EC
able dust)		dust)		
	Further information: Carcinogens or mutagens			

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
Silicic acid, potassium salt	Consumers	Inhalation	Long-term systemic effects	1,38 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,74 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0,74 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	5,61 mg/m3
	Workers	Skin contact	Long-term systemic effects	1,49 mg/kg bw/day
Kaolin, calcined	Workers	Inhalation	Acute systemic effects	3,00 mg/m3
	Workers	Inhalation	Acute local effects	3,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	3,00 mg/m3
	Workers	Inhalation	Long-term local effects	3,00 mg/m3
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Silicic acid, potassium salt	Sea water	1 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

	Intermittent use/release	7,5 mg/l
	Fresh water	7,5 mg/l
	Sewage treatment plant	348 mg/l
Kaolin, calcined	Intermittent use/release	25 mg/l
	Fresh water	4,1 mg/l
	Sea water	0,41 mg/l
	Sewage treatment plant	1400 mg/l
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l

### 8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

DGUV Regulation 112-190 - Use of breathing equipment

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state liquid

Color white

Odor characteristic

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range ca. 100 °C

Upper explosion limit / Upper : not determined

flammability limit

Lower explosion limit / Lower

flammability limit

not determined

Flash point Not applicable

Autoignition temperature not determined

Decomposition temperature Not applicable

рΗ 11,3 (20 °C)

Concentration: >= 0,0000 %

Method: DIN EN ISO 19396-1:2020-05

(as a dispersion)

Viscosity

Viscosity, dynamic > 0,000 mPa.s (20 °C)

Method: ISO 3219

Viscosity, kinematic not determined

Flow time not determined

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,34 g/cm3 (20 °C)

Method: DIN EN ISO 2811-1

Bulk density : Not applicable

Relative vapor density : not determined

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

Evaporation rate : Not applicable

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

#### 10.4 Conditions to avoid

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

Not classified based on available information.

## STOT-repeated exposure

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

### 11.2 Information on other hazards

# **Endocrine disrupting properties**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of liquid material residues at the collection point for

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

old paints/varnishes, dispose of dried material residues as construction and demolition waste or as municipal waste or

household waste.

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11\*

## **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

### Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

IATA (Cargo) Not regulated as a dangerous good IATA (Passenger) Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks Not classified as dangerous in the meaning of transport regu-

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High

Concern for Authorization (Article 59).

None

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

ny)

WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

: M-SK01 1-K silicate paints

: BSW40 Coating materials, water-based, alkaline

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,58 %

Volatile organic compounds : Directive 2004/42/EC

< 1 % < 10 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H315 : Causes skin irritation.

H319 : Causes serious eye irritation. H335 : May cause respiratory irritation.

H351 : Suspected of causing cancer if inhaled.

H372 : Causes damage to organs through prolonged or repeated

exposure if inhaled.

## Full text of other abbreviations

Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2004/37/EC / TWA : Long term exposure limit

DE DFG MAK / MAK : MAK value

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Prac-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

tice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### **Further information**

Other information

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European

Communities

SAX'S - Dangerous properties of industrial materials GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the Ger-

man Social Accident Insurance) Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

## Silikat Fassadenfarbe

Version Revision Date: SDS Number: Date of last issue: 25.10.2024 4.2 30.10.2024 6003514 Date of first issue: 28.03.2019

## **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN