

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Lasur-Spray Farblos

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Spray paint

Recommended restrictions : within adequate application - none  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Alpina Farben GmbH  
Roßdörfer Straße 50  
64372 OBER RAMSTADT

Telephone : +498001238887  
Telefax : +4961547170632

E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblös

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

Hazard Statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.

### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Additional Labeling

EUH208 Contains maleic anhydride, Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67, cobalt bis(2-ethylhexanoate), Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name                                                                                                          | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number                                                   | Classification                                                                                                                                                               | Concentration<br>(% w/w) |
|------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha                                    | 64742-48-9<br>265-150-3<br>649-327-00-6<br>01-2119457273-39,<br>01-2119463258-33,<br>01-2119486659-16   | Asp. Tox. 1; H304<br>EUH066                                                                                                                                                  | >= 30 - < 50             |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha                                    | 64742-48-9<br>265-150-3<br>649-327-00-6<br>01-2119457273-39,<br>01-2119463258-33                        | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>Asp. Tox. 1; H304<br>EUH066                                                                                                         | >= 1 - < 10              |
| Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67                                                              | Not Assigned<br>400-830-7<br>607-176-00-3<br>01-0000015075-76,<br>01-2119396032-43,<br>01-2119472279-28 | Skin Sens. 1; H317<br>Aquatic Chronic 2;<br>H411                                                                                                                             | >= 0,1 - < 0,25          |
| cobalt bis(2-ethylhexanoate)                                                                                           | 136-52-7<br>205-250-6<br>01-2119524678-29                                                               | Eye Irrit. 2; H319<br>Skin Sens. 1A; H317<br>Repr. 1B; H360FD<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 3;<br>H412                                                      | >= 0,025 - < 0,1         |
| Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 1065336-91-5<br>915-687-0<br>01-2119491304-40                                                           | Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>Repr. 2; H361f                                                                              | >= 0,025 - < 0,1         |
| maleic anhydride                                                                                                       | 108-31-6<br>203-571-6<br>607-096-00-9<br>01-2119472428-31,<br>01-2120759691-45                          | Acute Tox. 4; H302<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Resp. Sens. 1; H334<br>Skin Sens. 1A; H317<br>STOT RE 1; H372<br>(Respiratory system, Inhalation)<br>EUH071 | < 0,001                  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblös

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

|                                              |                                                           |                                                                  |             |
|----------------------------------------------|-----------------------------------------------------------|------------------------------------------------------------------|-------------|
|                                              |                                                           | specific concentration limit<br>Skin Sens. 1A; H317<br>≥ 0,001 % |             |
| Substances with a workplace exposure limit : |                                                           |                                                                  |             |
| dimethyl ether                               | 115-10-6<br>204-065-8<br>603-019-00-8<br>01-2119472128-37 | Flam. Gas 1A; H220<br>Press. Gas Compr. Gas; H280                | ≥ 30 - < 50 |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : If symptoms persist, call a physician.  
Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.  
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

#### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Standard procedure for chemical fires.  
In the event of fire and/or explosion do not breathe fumes.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.  
Ensure adequate ventilation.  
Remove all sources of ignition.

#### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Provide sufficient air exchange and/or exhaust in work rooms.

Please follow the technical information.

Advice on protection against fire and explosion : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in accordance with the particular national regulations.  
Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 2B

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                                           | CAS-No.    | Value type (Form of exposure) | Control parameters    | Basis       |
|------------------------------------------------------|------------|-------------------------------|-----------------------|-------------|
| Naphtha (petroleum), hydrotreated heavy; Low boiling | 64742-48-9 | AGW                           | 300 mg/m <sup>3</sup> | DE TRGS 900 |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

Version 3.1      Revision Date: 19.01.2023      SDS Number: 6001839      Date of last issue: 28.06.2022  
Date of first issue: 10.12.2019

|                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                     |                           |                          |             |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------------------|-------------|
| point ydrogen treated naphtha                                                      |                                                                                                                                                                                                                                                                                                                                                                                     |                           |                          |             |
|                                                                                    | Peak-limit category: 2;(II)                                                                                                                                                                                                                                                                                                                                                         |                           |                          |             |
|                                                                                    | Further information: Group exposure limit for hydrocarbon solvent mixtures                                                                                                                                                                                                                                                                                                          |                           |                          |             |
| dimethyl ether                                                                     | 115-10-6                                                                                                                                                                                                                                                                                                                                                                            | TWA                       | 1.000 ppm<br>1.920 mg/m3 | 2000/39/EC  |
|                                                                                    | Further information: Indicative                                                                                                                                                                                                                                                                                                                                                     |                           |                          |             |
|                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                     | AGW                       | 1.000 ppm<br>1.900 mg/m3 | DE TRGS 900 |
|                                                                                    | Peak-limit category: 8;(II)                                                                                                                                                                                                                                                                                                                                                         |                           |                          |             |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha | 64742-48-9                                                                                                                                                                                                                                                                                                                                                                          | AGW                       | 300 mg/m3                | DE TRGS 900 |
|                                                                                    | Peak-limit category: 2;(II)                                                                                                                                                                                                                                                                                                                                                         |                           |                          |             |
|                                                                                    | Further information: Group exposure limit for hydrocarbon solvent mixtures                                                                                                                                                                                                                                                                                                          |                           |                          |             |
| maleic anhydride                                                                   | 108-31-6                                                                                                                                                                                                                                                                                                                                                                            | AGW (Vapour and aerosols) | 0,02 ppm<br>0,081 mg/m3  | DE TRGS 900 |
|                                                                                    | Peak-limit category: 1; =2.5=(I)                                                                                                                                                                                                                                                                                                                                                    |                           |                          |             |
|                                                                                    | Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system |                           |                          |             |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name                                            | End Use   | Routes of exposure | Potential health effects   | Value               |
|-----------------------------------------------------------|-----------|--------------------|----------------------------|---------------------|
| dimethyl ether                                            | Consumers | Inhalation         | Long-term systemic effects | 471,00 mg/m3        |
|                                                           | Workers   | Inhalation         | Long-term systemic effects | 1894,00 mg/m3       |
| Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67 | Workers   | Inhalation         | Long-term systemic effects | 350,00 µg/m3        |
|                                                           | Consumers | Inhalation         | Long-term systemic effects | 85,00 µg/m3         |
|                                                           | Workers   | Skin contact       | Long-term systemic effects | 250,00 µg/kg bw/day |
| cobalt bis(2-ethylhexanoate)                              | Consumers | Inhalation         | Long-term local effects    | 37,00 µg/m3         |
|                                                           | Consumers | Ingestion          | Long-term systemic effects | 55,80 µg/kg bw/day  |
|                                                           | Workers   | Inhalation         | Long-term local effects    | 235,10 µg/m3        |
| Reaction mass of Bis(1,2,2,6,6-                           | Consumers | Inhalation         | Acute local effects        | 0,58 mg/m3          |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

Version 3.1      Revision Date: 19.01.2023      SDS Number: 6001839      Date of last issue: 28.06.2022  
Date of first issue: 10.12.2019

|                                                                                         |           |              |                            |                   |
|-----------------------------------------------------------------------------------------|-----------|--------------|----------------------------|-------------------|
| pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate |           |              |                            |                   |
|                                                                                         | Consumers | Ingestion    | Long-term systemic effects | 1,25 mg/kg bw/day |
|                                                                                         | Consumers | Inhalation   | Long-term systemic effects | 0,58 mg/m3        |
|                                                                                         | Consumers | Inhalation   | Acute systemic effects     | 0,58 mg/m3        |
|                                                                                         | Consumers | Skin contact | Long-term systemic effects | 1,25 mg/kg bw/day |
|                                                                                         | Consumers | Skin contact | Acute systemic effects     | 1,25 mg/kg bw/day |
|                                                                                         | Consumers | Ingestion    | Acute systemic effects     | 1,25 mg/kg bw/day |
|                                                                                         | Workers   | Inhalation   | Acute systemic effects     | 2,35 mg/m3        |
|                                                                                         | Workers   | Inhalation   | Acute local effects        | 2,35 mg/m3        |
|                                                                                         | Workers   | Inhalation   | Long-term systemic effects | 2,35 mg/m3        |
|                                                                                         | Workers   | Skin contact | Acute systemic effects     | 2,50 mg/kg bw/day |
|                                                                                         | Workers   | Skin contact | Long-term systemic effects | 2,50 mg/kg bw/day |
| maleic anhydride                                                                        | Consumers | Inhalation   | Long-term systemic effects | 0,05 mg/m3        |
|                                                                                         | Consumers | Ingestion    | Long-term systemic effects | 0,06 mg/kg bw/day |
|                                                                                         | Consumers | Ingestion    | Acute systemic effects     | 0,10 mg/kg bw/day |
|                                                                                         | Consumers | Skin contact | Acute systemic effects     | 0,10 mg/kg bw/day |
|                                                                                         | Consumers | Inhalation   | Long-term local effects    | 0,08 mg/m3        |
|                                                                                         | Consumers | Skin contact | Long-term systemic effects | 0,10 mg/kg bw/day |
|                                                                                         | Workers   | Inhalation   | Acute systemic effects     | 0,80 mg/m3        |
|                                                                                         | Workers   | Inhalation   | Acute systemic effects     | 0,95 mg/m3        |
|                                                                                         | Workers   | Inhalation   | Acute local effects        | 0,80 mg/m3        |
|                                                                                         | Workers   | Inhalation   | Long-term systemic effects | 0,40 mg/m3        |
|                                                                                         | Workers   | Inhalation   | Long-term systemic effects | 0,19 mg/m3        |
|                                                                                         | Workers   | Inhalation   | Long-term local effects    | 0,40 mg/m3        |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

Version 3.1      Revision Date: 19.01.2023      SDS Number: 6001839      Date of last issue: 28.06.2022  
Date of first issue: 10.12.2019

|  |           |              |                            |                   |
|--|-----------|--------------|----------------------------|-------------------|
|  | Workers   | Inhalation   | Long-term local effects    | 0,32 mg/m3        |
|  | Workers   | Skin contact | Acute systemic effects     | 0,20 mg/kg bw/day |
|  | Workers   | Skin contact | Long-term systemic effects | 0,20 mg/kg bw/day |
|  | Consumers | Inhalation   | Acute systemic effects     |                   |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name                                                                                                         | Environmental Compartment | Value                          |
|------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------------------------|
| dimethyl ether                                                                                                         | Sea sediment              | 0,069 mg/kg dry weight (d.w.)  |
|                                                                                                                        | Intermittent use/release  | 1,549 mg/l                     |
|                                                                                                                        | Sea water                 | 0,016 mg/l                     |
|                                                                                                                        | Fresh water               | 0,155 mg/l                     |
|                                                                                                                        | Sewage treatment plant    | 160 mg/l                       |
|                                                                                                                        | Fresh water sediment      | 0,681 mg/kg dry weight (d.w.)  |
|                                                                                                                        | Soil                      | 0,045 mg/kg dry weight (d.w.)  |
| cobalt bis(2-ethylhexanoate)                                                                                           | Sea water                 | 2,36 µg/l                      |
|                                                                                                                        | Soil                      | 10,9 mg/kg dry weight (d.w.)   |
|                                                                                                                        | Sea sediment              | 9,5 mg/kg dry weight (d.w.)    |
|                                                                                                                        | Fresh water               | 0,6 µg/l                       |
|                                                                                                                        | Sewage treatment plant    | 0,37 mg/l                      |
|                                                                                                                        | Fresh water sediment      | 9,5 mg/kg dry weight (d.w.)    |
| Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Sea water                 | 0,00022 mg/l                   |
|                                                                                                                        | Soil                      | 0,21 mg/kg dry weight (d.w.)   |
|                                                                                                                        | Fresh water               | 0,0022 mg/l                    |
|                                                                                                                        | Sewage treatment plant    | 1 mg/l                         |
|                                                                                                                        | Fresh water sediment      | 1,05 mg/kg dry weight (d.w.)   |
|                                                                                                                        | Intermittent use/release  | 0,009 mg/l                     |
|                                                                                                                        | Sea sediment              | 0,11 mg/kg dry weight (d.w.)   |
| maleic anhydride                                                                                                       | Fresh water               | 0,075 mg/l                     |
|                                                                                                                        | Fresh water sediment      | 0,334 mg/kg dry weight (d.w.)  |
|                                                                                                                        | Soil                      | 0,0415 mg/kg dry weight (d.w.) |
|                                                                                                                        | Sea water                 | 0,01 mg/l                      |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblös

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

|  |                          |                                |
|--|--------------------------|--------------------------------|
|  | Intermittent use/release | 0,4281 mg/l                    |
|  | Sewage treatment plant   | 44,6 mg/l                      |
|  | Soil                     | 0,01 mg/kg dry weight (d.w.)   |
|  | Sea water                | 0,0075 mg/l                    |
|  | Secondary Poisoning      | 6,67 mg/kg food                |
|  | Fresh water              | 0,1 mg/l                       |
|  | Sewage treatment plant   | 4,46 mg/l                      |
|  | Sea sediment             | 0,006 mg/kg dry weight (d.w.)  |
|  | Fresh water sediment     | 0,06 mg/kg dry weight (d.w.)   |
|  | Intermittent use/release | 0,75 mg/l                      |
|  | Sea sediment             | 0,0334 mg/kg dry weight (d.w.) |

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks

: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection

: Safety shoes  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection

: DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|                                                  |                               |
|--------------------------------------------------|-------------------------------|
| Physical state                                   | : aerosol                     |
| Color                                            | : various                     |
| Odor                                             | : No data available           |
| Odor Threshold                                   | : Not relevant                |
| Melting point/freezing point                     | : not determined              |
| Boiling point/boiling range                      | : -24,9 °C                    |
| Flammability                                     | : Sustains combustion         |
| Upper explosion limit / Upper flammability limit | : 18,6 %(V)                   |
| Lower explosion limit / Lower flammability limit | : 3 %(V)                      |
| Flash point                                      | : < 0 °C                      |
| Autoignition temperature                         | : not determined              |
| Decomposition temperature                        | : Not applicable              |
| pH                                               | : 6,95<br>Concentration: 10 % |
| Viscosity                                        |                               |
| Viscosity, dynamic                               | : No data available           |
| Viscosity, kinematic                             | : not determined              |
| Solubility(ies)                                  |                               |
| Water solubility                                 | : immiscible                  |
| Partition coefficient: n-octanol/water           | : not determined              |
| Vapor pressure                                   | : 3.400 hPa                   |
| Relative density                                 | : not determined              |
| Density                                          | : 0,801 g/cm <sup>3</sup>     |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

Relative vapor density : not determined

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Evaporation rate : Not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.  
Hazardous decomposition products formed under fire conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Risk of bursting.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Protect from frost, heat and sunlight.

Risk of bursting.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblös

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Components:

##### maleic anhydride:

Acute oral toxicity : LD50 (Rat, male and female): 1.090 mg/kg  
Method: OECD Test Guideline 401

##### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

##### Components:

##### maleic anhydride:

Species : Rabbit  
Assessment : Causes burns.

##### Serious eye damage/eye irritation

Not classified based on available information.

##### Components:

##### maleic anhydride:

Species : Rabbit  
Assessment : Causes burns.

##### Respiratory or skin sensitization

##### Skin sensitization

Not classified based on available information.

##### Respiratory sensitization

Not classified based on available information.

##### Components:

##### maleic anhydride:

Species : Rat  
Result : Causes sensitization.

##### Germ cell mutagenicity

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

No data available

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

#### **Components:**

##### **maleic anhydride:**

Partition coefficient: n-octanol/water : log Pow: -2,61 (19,8 °C)  
pH: 4 - 9

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : .  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080111\*, waste paint and varnish containing organic solvents or other dangerous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1950  
ADR : UN 1950  
RID : UN 1950  
IMDG : UN 1950  
IATA : UN 1950

### 14.2 UN proper shipping name

ADN : AEROSOLS

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

**ADR** : AEROSOLS

**RID** : AEROSOLS

**IMDG** : AEROSOLS

**IATA** :

### 14.3 Transport hazard class(es)

|             | Class | Subsidiary risks |
|-------------|-------|------------------|
| <b>ADN</b>  | : 2   | 2.1              |
| <b>ADR</b>  | : 2   | 2.1              |
| <b>RID</b>  | : 2   | 2.1              |
| <b>IMDG</b> | : 2.2 |                  |
| <b>IATA</b> | : 2.2 |                  |

### 14.4 Packing group

#### **ADN**

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

#### **ADR**

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

#### **RID**

Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

#### **IMDG**

Packing group : Not assigned by regulation  
Labels : 2.2  
EmS Code : F-D, S-U

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Non-flammable, non-toxic Gas

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

Packing group : Not assigned by regulation  
Labels : Non-flammable, non-toxic Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

according to Regulation (EC) No. 1907/2006



DE / EN

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

|                              |                                    |
|------------------------------|------------------------------------|
| Water hazard class (Germany) | : WGK 1 slightly water endangering |
| Volatile organic compounds   | : < 71 %<br>< 840 g/l              |

**Other regulations:**

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

|      |   |                                                                            |
|------|---|----------------------------------------------------------------------------|
| H220 | : | Extremely flammable gas.                                                   |
| H226 | : | Flammable liquid and vapor.                                                |
| H280 | : | Contains gas under pressure; may explode if heated.                        |
| H302 | : | Harmful if swallowed.                                                      |
| H304 | : | May be fatal if swallowed and enters airways.                              |
| H314 | : | Causes severe skin burns and eye damage.                                   |
| H317 | : | May cause an allergic skin reaction.                                       |
| H318 | : | Causes serious eye damage.                                                 |
| H319 | : | Causes serious eye irritation.                                             |
| H334 | : | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H336 | : | May cause drowsiness or dizziness.                                         |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

|        |                                                                   |
|--------|-------------------------------------------------------------------|
| H360FD | : May damage fertility. May damage the unborn child.              |
| H361f  | : Suspected of damaging fertility.                                |
| H372   | : Causes damage to organs through prolonged or repeated exposure. |
| H400   | : Very toxic to aquatic life.                                     |
| H410   | : Very toxic to aquatic life with long lasting effects.           |
| H411   | : Toxic to aquatic life with long lasting effects.                |
| H412   | : Harmful to aquatic life with long lasting effects.              |
| EUH066 | : Repeated exposure may cause skin dryness or cracking.           |
| EUH071 | : Corrosive to the respiratory tract.                             |

### Full text of other abbreviations

|                   |                                                                                                                      |
|-------------------|----------------------------------------------------------------------------------------------------------------------|
| Acute Tox.        | : Acute toxicity                                                                                                     |
| Aquatic Acute     | : Short-term (acute) aquatic hazard                                                                                  |
| Aquatic Chronic   | : Long-term (chronic) aquatic hazard                                                                                 |
| Asp. Tox.         | : Aspiration hazard                                                                                                  |
| Eye Dam.          | : Serious eye damage                                                                                                 |
| Eye Irrit.        | : Eye irritation                                                                                                     |
| Flam. Gas         | : Flammable gases                                                                                                    |
| Flam. Liq.        | : Flammable liquids                                                                                                  |
| Press. Gas        | : Gases under pressure                                                                                               |
| Repr.             | : Reproductive toxicity                                                                                              |
| Resp. Sens.       | : Respiratory sensitization                                                                                          |
| Skin Corr.        | : Skin corrosion                                                                                                     |
| Skin Sens.        | : Skin sensitization                                                                                                 |
| STOT RE           | : Specific target organ toxicity - repeated exposure                                                                 |
| STOT SE           | : Specific target organ toxicity - single exposure                                                                   |
| 2000/39/EC        | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| DE TRGS 900       | : Germany. TRGS 900 - Occupational exposure limit values.                                                            |
| 2000/39/EC / TWA  | : Limit Value - eight hours                                                                                          |
| DE TRGS 900 / AGW | : Time Weighted Average                                                                                              |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

### Other information:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Lasur-Spray Farblos

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.06.2022  |
| 3.1     | 19.01.2023     | 6001839     | Date of first issue: 10.12.2019 |

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

### Classification of the mixture:

Aerosol 1

H222, H229

### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN