

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

|                                 |   |                                      |
|---------------------------------|---|--------------------------------------|
| Trade name                      | : | AP FF Lack Held des Waldes Sprühlack |
| Unique Formula Identifier (UFI) | : | YUUS-5PCV-0011-0E3Q                  |

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

|                                 |   |                                    |
|---------------------------------|---|------------------------------------|
| Use of the Substance/Mixture    | : | Spray paint                        |
| Recommended restrictions on use | : | within adequate application - none |

#### 1.3 Details of the supplier of the safety data sheet

|                                           |   |                                                                  |
|-------------------------------------------|---|------------------------------------------------------------------|
| Company                                   | : | Alpina Farben GmbH<br>Roßdörfer Straße 50<br>64372 OBER RAMSTADT |
| Telephone                                 | : | +498001238887                                                    |
| Telefax                                   | : | +4961547170632                                                   |
| Website                                   | : | www.alpina-farben.de                                             |
| E-mail address Responsible/issuing person | : | msds@dr-rmi.com                                                  |

#### 1.4 Emergency telephone

|                       |   |                       |
|-----------------------|---|-----------------------|
| Emergency telephone 1 | : | +49613284463 GBK GmbH |
|-----------------------|---|-----------------------|

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                            |                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------|
| Aerosols, Category 1       | H222: Extremely flammable aerosol.<br>H229: Pressurised container: May burst if heated. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation.                                                    |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

|      |                                             |
|------|---------------------------------------------|
| H222 | Extremely flammable aerosol.                |
| H229 | Pressurised container: May burst if heated. |
| H319 | Causes serious eye irritation.              |

Precautionary Statements

:

|      |                                                                       |
|------|-----------------------------------------------------------------------|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children.                                        |

### Prevention:

|      |                                                                                                |
|------|------------------------------------------------------------------------------------------------|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source.                                        |
| P251 | Do not pierce or burn, even after use.                                                         |

### Storage:

|             |                                                                               |
|-------------|-------------------------------------------------------------------------------|
| P410 + P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. |
|-------------|-------------------------------------------------------------------------------|

### Additional Labeling

|        |                                                                                                                                           |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------|
| EUH208 | Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. |
| EUH211 | Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.                                          |

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name                                                                                            | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number       | Classification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Concentration<br>(% w/w) |
|----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| ethanol                                                                                                  | 64-17-5<br>200-578-6<br>603-002-00-5<br>01-2119457610-43    | Eye Irrit. 2; H319<br>Flam. Liq. 2; H225                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | >= 20 - < 30             |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7<br>236-675-5<br>022-006-00-2<br>01-2119489379-17 | Carc. 2; H351                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | >= 1 - < 10              |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)            | 55965-84-9<br><br>613-167-00-5<br>01-2120764691-48          | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Acute Tox. 2; H310<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410<br>EUH071<br><br>M-Factor (Acute aquatic toxicity): 100<br>M-Factor (Chronic aquatic toxicity): 100<br><br>specific concentration limit<br>Skin Corr. 1C; H314<br>>= 0,6 %<br>Skin Irrit. 2; H315<br>0,06 - < 0,6 %<br>Eye Irrit. 2; H319<br>0,06 - < 0,6 %<br>Skin Sens. 1A; H317<br>>= 0,0015 %<br>Eye Dam. 1; H318<br>>= 0,6 % | >= 0,0002 - < 0,0015     |
| Substances with a workplace exposure limit :                                                             |                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                          |
| dimethyl ether                                                                                           | 115-10-6<br>204-065-8                                       | Flam. Gas 1A; H220<br>Press. Gas Compr.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | >= 30 - < 50             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

|  |                                  |           |  |
|--|----------------------------------|-----------|--|
|  | 603-019-00-8<br>01-2119472128-37 | Gas; H280 |  |
|--|----------------------------------|-----------|--|

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- |                         |                                                                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice          | : Never give anything by mouth to an unconscious person.<br>If you feel unwell, seek medical advice (show the label where possible).<br>Move out of dangerous area.<br>First aider needs to protect himself. |
| If inhaled              | : If symptoms persist, call a physician.<br>Move to fresh air.                                                                                                                                               |
| In case of skin contact | : Do NOT use solvents or thinners.<br>In case of contact, immediately flush skin with soap and plenty of water.<br>Take off all contaminated clothing immediately.                                           |
| In case of eye contact  | : If eye irritation persists: Get medical advice/ attention.<br>IF IN EYES: Rinse cautiously with water for several minutes.<br>Remove contact lenses, if present and easy to do. Continue rinsing.          |
| If swallowed            | : Seek medical advice.<br>Clean mouth with water and drink afterwards plenty of water.<br>If swallowed, DO NOT induce vomiting.                                                                              |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |       |                                  |
|-------|----------------------------------|
| Risks | : Causes serious eye irritation. |
|-------|----------------------------------|

#### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |                             |
|-----------|-----------------------------|
| Treatment | : No information available. |
|-----------|-----------------------------|

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- |                                |                                                                                                                                                                                       |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media   | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. |
| Unsuitable extinguishing media | : None known.                                                                                                                                                                         |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

---

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Standard procedure for chemical fires.  
In the event of fire and/or explosion do not breathe fumes.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.  
Ensure adequate ventilation.  
Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.  
, For personal protection see section 8., For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Provide sufficient air exchange and/or exhaust in work rooms.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

Advice on protection against fire and explosion : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in accordance with the particular national regulations. Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 2B

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components     | CAS-No.                                                                                                                                                                                                                                    | Value type (Form of exposure) | Control parameters                   | Basis       |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--------------------------------------|-------------|
| dimethyl ether | 115-10-6                                                                                                                                                                                                                                   | TWA                           | 1.000 ppm<br>1.920 mg/m <sup>3</sup> | 2000/39/EC  |
|                | Further information: Indicative                                                                                                                                                                                                            |                               |                                      |             |
|                |                                                                                                                                                                                                                                            | AGW                           | 1.000 ppm<br>1.900 mg/m <sup>3</sup> | DE TRGS 900 |
|                | Peak-limit category: 8;(II)                                                                                                                                                                                                                |                               |                                      |             |
|                |                                                                                                                                                                                                                                            | MAK                           | 1.000 ppm<br>1.900 mg/m <sup>3</sup> | DE DFG MAK  |
|                | Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C |                               |                                      |             |
| ethanol        | 64-17-5                                                                                                                                                                                                                                    | AGW                           | 200 ppm<br>380 mg/m <sup>3</sup>     | DE TRGS 900 |
|                | Peak-limit category: 4;(II)                                                                                                                                                                                                                |                               |                                      |             |
|                | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child                                                                                                   |                               |                                      |             |
|                |                                                                                                                                                                                                                                            | MAK                           | 200 ppm<br>380 mg/m <sup>3</sup>     | DE DFG MAK  |
|                | Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value                                                                                      |                               |                                      |             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

Version 2.0      Revision Date: 09.04.2025      SDS Number: 6024921      Date of last issue: 12.01.2023  
Date of first issue: 09.04.2021

|                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                             |                                          |                                              |             |
|-------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|----------------------------------------------|-------------|
|                                                                                                                         | can be derived, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed, Germ cell mutagens or suspected substances (according to the definition of Category 3 A and 3B), the potency of which is considered to be so low that, provided the MAK and BAT values are observed, their contribution to genetic risk for man is considered to be very slight |                                          |                                              |             |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | 13463-67-7                                                                                                                                                                                                                                                                                                                                                                                  | MAK (measured as the alveolate fraction) | 0,3 mg/m <sup>3</sup>                        | DE DFG MAK  |
|                                                                                                                         | Peak-limit category: 8; II                                                                                                                                                                                                                                                                                                                                                                  |                                          |                                              |             |
|                                                                                                                         | Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed                                                                                                                           |                                          |                                              |             |
|                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                             | AGW (Inhalable fraction)                 | 10 mg/m <sup>3</sup><br>(Titanium dioxide)   | DE TRGS 900 |
|                                                                                                                         | Peak-limit category: 2;(II)                                                                                                                                                                                                                                                                                                                                                                 |                                          |                                              |             |
|                                                                                                                         | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child                                                                                                                                                                                                                                                    |                                          |                                              |             |
|                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                             | AGW (Alveolate fraction)                 | 1,25 mg/m <sup>3</sup><br>(Titanium dioxide) | DE TRGS 900 |
|                                                                                                                         | Peak-limit category: 2;(II)                                                                                                                                                                                                                                                                                                                                                                 |                                          |                                              |             |
|                                                                                                                         | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child                                                                                                                                                                                                                                                    |                                          |                                              |             |
|                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                             | BM (Alveolar dust fraction)              | 0,5 mg/m <sup>3</sup>                        | DE TRGS 527 |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name                                                                                                          | End Use   | Routes of exposure | Potential health effects   | Value                     |
|-------------------------------------------------------------------------------------------------------------------------|-----------|--------------------|----------------------------|---------------------------|
| dimethyl ether                                                                                                          | Consumers | Inhalation         | Long-term systemic effects | 471,00 mg/m <sup>3</sup>  |
|                                                                                                                         | Workers   | Inhalation         | Long-term systemic effects | 1894,00 mg/m <sup>3</sup> |
| ethanol                                                                                                                 | Consumers | Inhalation         | Acute local effects        | 950,00 mg/m <sup>3</sup>  |
|                                                                                                                         | Workers   | Inhalation         | Acute local effects        | 1900,00 mg/m <sup>3</sup> |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | Consumers | Ingestion          | Long-term systemic effects | 700,00 mg/kg bw/day       |
|                                                                                                                         | Workers   | Inhalation         | Long-term local effects    | 10,00 mg/m <sup>3</sup>   |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------|---------------------------|-------|
|----------------|---------------------------|-------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

|                                                                                                                         |                          |                               |
|-------------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------|
| dimethyl ether                                                                                                          | Sea sediment             | 0,069 mg/kg dry weight (d.w.) |
|                                                                                                                         | Intermittent use/release | 1,549 mg/l                    |
|                                                                                                                         | Sea water                | 0,016 mg/l                    |
|                                                                                                                         | Fresh water              | 0,155 mg/l                    |
|                                                                                                                         | Sewage treatment plant   | 160 mg/l                      |
|                                                                                                                         | Fresh water sediment     | 0,681 mg/kg dry weight (d.w.) |
|                                                                                                                         | Soil                     | 0,045 mg/kg dry weight (d.w.) |
| ethanol                                                                                                                 | Sea sediment             | 2,9 mg/kg dry weight (d.w.)   |
|                                                                                                                         | Sewage treatment plant   | 580 mg/l                      |
|                                                                                                                         | Fresh water sediment     | 3,6 mg/kg dry weight (d.w.)   |
|                                                                                                                         | Sea water                | 0,79 mg/l                     |
|                                                                                                                         | Soil                     | 0,63 mg/kg dry weight (d.w.)  |
|                                                                                                                         | Intermittent use/release | 2,75 mg/l                     |
|                                                                                                                         | Fresh water              | 0,96 mg/l                     |
|                                                                                                                         | Secondary Poisoning      | 0,72 g/kg food                |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | Sewage treatment plant   | 100 mg/l                      |
|                                                                                                                         | Fresh water              | 0,184 mg/l                    |
|                                                                                                                         | Soil                     | 100 mg/kg dry weight (d.w.)   |
|                                                                                                                         | Sea water                | 0,0184 mg/l                   |
|                                                                                                                         | Fresh water sediment     | 1000 mg/kg dry weight (d.w.)  |
|                                                                                                                         | Sea sediment             | 100 mg/kg dry weight (d.w.)   |
|                                                                                                                         | Intermittent use/release | 0,193 mg/l                    |

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

Hand protection

|                  |                  |
|------------------|------------------|
| Material         | : Nitrile rubber |
| Glove thickness  | : 0,2 mm         |
| Protective index | : Class 3        |

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : During spray application: Do not breathe spray dust. Use  
A2/P2 combination filter for paint spraying.

DGUV Regulation 112-190 - Use of breathing equipment

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|                                                  |                       |
|--------------------------------------------------|-----------------------|
| Physical state                                   | : aerosol             |
| Color                                            | : white               |
| Odor                                             | : No data available   |
| Odor Threshold                                   | : Not relevant        |
| Melting point/freezing point                     | : not determined      |
| Boiling point/boiling range                      | : not determined      |
| Flammability                                     | : Sustains combustion |
| Upper explosion limit / Upper flammability limit | : not determined      |
| Lower explosion limit / Lower flammability limit | : not determined      |
| Flash point                                      | : -42 °C              |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

---

|                                        |   |                             |
|----------------------------------------|---|-----------------------------|
| Autoignition temperature               | : | not determined              |
| Decomposition temperature              | : | Not applicable              |
| pH                                     | : | 6,95<br>Concentration: 10 % |
| Viscosity                              | : |                             |
| Viscosity, dynamic                     | : | No data available           |
| Solubility(ies)                        | : |                             |
| Water solubility                       | : | partly miscible             |
| Partition coefficient: n-octanol/water | : | not determined              |
| Vapor pressure                         | : | not determined              |
| Relative density                       | : | not determined              |
| Density                                | : | 0,916 g/cm <sup>3</sup>     |
| Relative vapor density                 | : | not determined              |

### 9.2 Other information

|                      |   |                |
|----------------------|---|----------------|
| Explosives           | : | Not applicable |
| Oxidizing properties | : | Not applicable |
| Evaporation rate     | : | Not applicable |

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.  
Hazardous decomposition products formed under fire conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Risk of bursting.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Protect from frost, heat and sunlight.

Risk of bursting.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

**Not classified based on available information.**

#### Components:

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

### Skin corrosion/irritation

|| Not classified based on available information.

### Serious eye damage/eye irritation

|| Causes serious eye irritation.

### Respiratory or skin sensitization

#### Skin sensitization

|| Not classified based on available information.

#### Respiratory sensitization

|| Not classified based on available information.

### Germ cell mutagenicity

|| Not classified based on available information.

### Carcinogenicity

|| Not classified based on available information.

### Reproductive toxicity

|| Not classified based on available information.

### STOT-single exposure

|| Not classified based on available information.

### STOT-repeated exposure

|| Not classified based on available information.

### Aspiration toxicity

|| Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

|| Not classified based on available information.

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic toxicity) : 100

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

---

M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **ethanol:**

Partition coefficient: n-octanol/water : log Pow: -0,35 (24 °C)  
pH: 7,4

##### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Partition coefficient: n-octanol/water : log Pow: <= 0,75  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

|                        |   |                                                                                                                                                                                                                                    |
|------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                | : | Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local, regional, national and international authorities.<br><br>Must not reach sewage system or environment. |
| Contaminated packaging | : | Only completely emptied containers should be given for recycling.                                                                                                                                                                  |
| Waste Code             | : | used product<br>080111*, waste paint and varnish containing organic solvents or other dangerous substances                                                                                                                         |

### SECTION 14: Transport information

#### 14.1 UN number or ID number

|      |   |         |
|------|---|---------|
| ADN  | : | UN 1950 |
| ADR  | : | UN 1950 |
| RID  | : | UN 1950 |
| IMDG | : | UN 1950 |
| IATA | : | UN 1950 |

#### 14.2 UN proper shipping name

|      |   |                     |
|------|---|---------------------|
| ADN  | : | AEROSOLS            |
| ADR  | : | AEROSOLS            |
| RID  | : | AEROSOLS            |
| IMDG | : | AEROSOLS            |
| IATA | : | Aerosols, flammable |

#### 14.3 Transport hazard class(es)

|      | Class | Subsidiary risks |
|------|-------|------------------|
| ADN  | :     | 2 2.1            |
| ADR  | :     | 2 2.1            |
| RID  | :     | 2 2.1            |
| IMDG | :     | 2.1              |
| IATA | :     | 2.1              |

#### 14.4 Packing group

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

### ADN

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

### ADR

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

### RID

Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

### IMDG

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : None

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

Water hazard class (Germany) : WGK 1 slightly water endangering

Volatile organic compounds : Volatile organic compounds (VOC) content: 56,95 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 1,51 %

Volatile organic compounds : < 57 %  
< 530 g/l

Directive 2004/42/EC  
< 56 %  
< 520 g/l

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

|        |                                                         |
|--------|---------------------------------------------------------|
| H220   | : Extremely flammable gas.                              |
| H225   | : Highly flammable liquid and vapor.                    |
| H280   | : Contains gas under pressure; may explode if heated.   |
| H301   | : Toxic if swallowed.                                   |
| H310   | : Fatal in contact with skin.                           |
| H314   | : Causes severe skin burns and eye damage.              |
| H317   | : May cause an allergic skin reaction.                  |
| H318   | : Causes serious eye damage.                            |
| H319   | : Causes serious eye irritation.                        |
| H330   | : Fatal if inhaled.                                     |
| H351   | : Suspected of causing cancer if inhaled.               |
| H400   | : Very toxic to aquatic life.                           |
| H410   | : Very toxic to aquatic life with long lasting effects. |
| EUH071 | : Corrosive to the respiratory tract.                   |

### Full text of other abbreviations

|                   |                                                                                                                      |
|-------------------|----------------------------------------------------------------------------------------------------------------------|
| Acute Tox.        | : Acute toxicity                                                                                                     |
| Aquatic Acute     | : Short-term (acute) aquatic hazard                                                                                  |
| Aquatic Chronic   | : Long-term (chronic) aquatic hazard                                                                                 |
| Carc.             | : Carcinogenicity                                                                                                    |
| Eye Dam.          | : Serious eye damage                                                                                                 |
| Eye Irrit.        | : Eye irritation                                                                                                     |
| Flam. Gas         | : Flammable gases                                                                                                    |
| Flam. Liq.        | : Flammable liquids                                                                                                  |
| Press. Gas        | : Gases under pressure                                                                                               |
| Skin Corr.        | : Skin corrosion                                                                                                     |
| Skin Sens.        | : Skin sensitization                                                                                                 |
| 2000/39/EC        | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| DE DFG MAK        | : Germany. MAK BAT Annex IIa                                                                                         |
| DE TRGS 527       | : Germany. TRGS 527 - Activities with nanomaterials                                                                  |
| DE TRGS 900       | : Germany. TRGS 900 - Occupational exposure limit values.                                                            |
| 2000/39/EC / TWA  | : Limit Value - eight hours                                                                                          |
| DE DFG MAK / MAK  | : MAK value                                                                                                          |
| DE TRGS 527 / BM  | : Assessment scale                                                                                                   |
| DE TRGS 900 / AGW | : Time Weighted Average                                                                                              |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community num-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

ber; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet : ECHA WebSite  
ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH  
NIOSH - Registry of toxic effects of chemical substances  
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX'S - Dangerous properties of industrial materials  
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)  
Toxnet - Toxicology Data Network

### Classification of the mixture:

|              |            |
|--------------|------------|
| Aerosol 1    | H222, H229 |
| Eye Irrit. 2 | H319       |

### Classification procedure:

|                    |
|--------------------|
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## AP FF Lack Held des Waldes Sprühlack

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.01.2023  |
| 2.0     | 09.04.2025     | 6024921     | Date of first issue: 09.04.2021 |

---

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our up-stream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN